

PN-EN 16002:2019-01/AC

Wprowadza

EN 16002:2018/AC:2021, IDT

Elastyczne wyroby wodochronne

**Określanie wytrzymałości na obciążenie wiatrem elastycznych
wyrobów do pokryć dachowych mocowanych mechanicznie**

Poprawka do Normy Europejskiej EN 16002:2018/AC:2021 *Flexible sheets for waterproofing --
Determination of the resistance to wind load of mechanically fastened flexible sheets for roof waterproofing*
ma status Poprawki do Polskiej Normy

Przedmowa krajowa

Niniejsza poprawka została zatwierdzona przez Prezesa PKN 10 listopada 2021 r.

Komitetem krajowym odpowiedzialnym za poprawkę jest PKN/KT 214 ds. Wyrobów Bitumicznych i Polimerowych do Izolacji Wodochronnych w Budownictwie.

Istnieje możliwość przetłumaczenia poprawki na język polski na wniosek zainteresowanych środowisk. Decyzję podejmuje właściwy Komitet Techniczny.

W sprawach merytorycznych dotyczących treści normy można zwracać się do właściwego Komitetu Technicznego lub właściwej Rady Sektorowej PKN, kontakt: www.pkn.pl.

Nota uznaniowa

Poprawka do Normy Europejskiej EN 16002:2018/AC:2021 została uznana przez PKN za Poprawkę do Polskiej Normy PN-EN 16002:2019-01/AC:2021-11.

Flexible sheets for waterproofing - Determination of the resistance to wind
load of mechanically fastened flexible sheets for roof waterproofing

Feuilles souples d'étanchéité - Détermination
de la résistance à l'arrachement au vent des
feuilles souples d'étanchéité de toiture fixées
mécaniquement

Abdichtungsbahnen - Bestimmung des
Widerstandes gegen Windlast von
mechanisch befestigten bahnenförmigen
Stoffen für die Dachabdichtung

This corrigendum becomes effective on 6 October 2021 for incorporation in the official English version of the EN.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

1 Modification to 8.4, Insulation

Replace the text of the two alineas below specification c) with:

“Other insulation materials may be used for the test but in this case the application rules as defined in Clause 11 are not applicable. In this case the insulation material which is used shall be specified in detail within the test report. These insulation boards shall be installed in such way that free airflow is ensured from the outside of the test sample to the total area between the insulation board and the underside of the waterproofing membrane.”.

2 Modification to Clause 12, Test report

Replace the text of information s) with:

“ description of how free airflow is ensured according to requirement in 8.4”;

Add below information s):

“t) any other factor that could have influenced the result.”.